

S.N. 09/834,061
William L. Post
Atty Dkt 10003807-1

Amendments to the Claims

1. (canceled)
2. (previously presented) The method of claim 21 wherein the current pixel location includes a current row and a current column; wherein the defective pixel location includes a defective pixel row and a defective pixel column; wherein the step of determining whether the current pixel location is a defective pixel location further comprises:
 - comparing the current row with the defective pixel row and comparing the current column with the defective pixel column;
 - determining whether there is a match between the current row and the defective pixel row; and
 - determining whether there is a match between the current column and the defective pixel column.
3. (previously presented) The method of claim 21 wherein the step of when the current pixel location is not a defective pixel location, providing a received pixel value as an output pixel value further comprises:
 - receiving a pixel value from an analog to digital converter; and
 - providing the received pixel value as an output pixel value.
4. (previously presented) The method of claim 21 wherein the step of when the current pixel location is a defective pixel location, providing a consistent replacement pixel value as the output pixel value further comprises:
 - providing a consistent replacement pixel value that is in the same frame, in the same row, and a predetermined number of pixels from the current pixel location as the output pixel value.

S.N. 09/834,061
William L. Post
Atty Dkt 10003807-1

5. (original) The method of claim 4 wherein the step of providing a previous pixel value that is in the same frame, in the same row, and a predetermined number of pixels from the current pixel location as the output pixel value further comprises:

providing a previous pixel value that has the same color as the current pixel and is two pixels to the left of the current pixel location as the output pixel value.

6. (previously presented) The method of claim 21 wherein the step of when the current pixel location is a defective pixel location, providing a consistent replacement pixel value as the output pixel value further comprises:

when the current pixel location is one of the first pixel location and the second pixel location of a row, providing a zero pixel value as the output pixel value.

7. (previously presented) The method of claim 21 wherein the step of when the current pixel location is a defective pixel location, providing a consistent replacement pixel value as the output pixel value further comprises:

employing a two step delay circuit to provide a replacement pixel value for the defective current pixel; wherein the two step delay circuit is reset to zero at the beginning of every row.

Claims 8-10 (canceled)

11. (currently amended) A circuit for correcting defective pixels in an array

S.N. 09/834,061
William L. Post
Atty Dkt 10003807-1

having a plurality of pixels comprising:

a defective pixel detection mechanism for providing a determination of whether a pixel is defective, the defective pixel detection mechanism having a table for storing a plurality of defective pixel ~~location~~ locations that do not vary from frame to frame; wherein the table has a plurality of entries, each entry having a row value and a column value, the plurality of entries including a last entry; wherein the row value of the last entry in the table is set to a value that is greater than the first predetermined number of rows; and the column value of the last entry in the table is set to a value that is greater than the second predetermined number of columns; wherein hardware to determine if the last entry in the table has been reached is obviated; and a defective pixel correction mechanism that replaces a current defective pixel with a consistent replacement pixel value from the same frame, on the same row, and a predetermined number of pixels from the current defective pixel;

wherein the defective pixel correction mechanism and the defective pixel detection mechanism eliminate one of artifacts that stem from inconsistent detection of defective pixel from frame to frame and artifacts that stem from inconsistent replacement of defective pixels.

12. (currently amended) The circuit of claim 11 wherein the defective pixel detection mechanism ~~includes~~ includes:

a match unit for receiving a current pixel location and a defective pixel location, comparing a current pixel location with a defective pixel location, asserting a match signal when there is a match, and de-asserting the match signal when there is no match.

13. (currently amended) The circuit of claim 12 wherein the defective pixel

S.N. 09/834,061
William L. Post
Atty Dkt 10003807-1

detection mechanism further ~~includes~~ includes:

an index manager coupled to the table and the match unit for receiving the match signal and responsive thereto for managing a table index that points to a current defective pixel location in the table.

14. (original) The circuit of claim 13 wherein the index manager, responsive to an asserted match signal, increments the table index so that the table index points to the next defective pixel location; and wherein the index manager has an input for receiving a start frame signal and responsive thereto for resetting the table index.

15. (currently amended) The circuit of claim 11 wherein the defective pixel detection mechanism ~~includes~~ includes:

a register coupled to the table for use in writing defective pixel locations to the table and reading defective pixel locations from the table.

16. (currently amended) The circuit of claim 12 wherein the defective pixel correction mechanism further ~~includes~~ includes:

a consistent replacement choice facility for generating a first output;
a source for providing a second output; and
a replacement unit coupled to the consistent replacement choice facility for receiving the first output, to the source for receiving the second output, and to the match unit for receiving the match signal; the replacement unit for selectively providing a first output and a second output as an output pixel value based on the match signal.

17. (original) The circuit of claim 16 wherein the replacement unit includes a multiplexer; and

S.N. 09/834,061
William L. Post
Atty Dkt 10003807-1

wherein the a consistent replacement choice facility includes a two step delay line having a one back circuit and a two back circuit for providing the first output to the multiplexer;

wherein the one back circuit and a two back circuit each includes an input for receiving a start row signal and responsive thereto for clearing the contents thereof.

18. (currently amended) The circuit of claim 12 wherein the source for providing a second output ~~includes~~ includes:

an analog to digital converter for providing a current pixel value as the second output.

19. (currently amended) The circuit of claim 11 wherein the circuit is couplable to an array of pixels having a first predetermined number of rows and a second predetermined number of columns;

wherein the table includes a plurality of defective pixel locations that are in a sorted order; wherein a search of the table to determine if a current pixel location is a defective pixel location is ~~obviated;~~ obviated.

20. (previously presented) An image sensor comprising:

(a) a sensor array having a plurality of pixels arranged in rows and columns; wherein at least one pixel is defective;

(b) a row selector coupled to the sensor array for selecting a row of the sensor array;

(c) a column selector coupled to the sensor array for selecting a column of the sensor array;

(d) a timing controller coupled to the row selector and column selector for providing control signals thereto;

(e) a defective pixel detection mechanism that employs a look-up table

S.N. 09/834,061
William L. Post
Atty Dkt 10003807-1

with defective pixel locations for providing a determination of whether a pixel is defective or non-defective; wherein the defective pixel locations do not vary from frame to frame; wherein the table has a plurality of entries, each entry having a row value and a column value, the plurality of entries including a last entry; wherein the row value of the last entry in the table is set to a value that is greater than the first predetermined number of rows; and the column value of the last entry in the table is set to a value that is greater than the second predetermined number of columns; wherein hardware to determine if the last entry in the table has been reached is obviated; and

f) a defective pixel correction mechanism coupled to the defective pixel detection mechanism that employs a consistent replacement choice facility for providing a consistent replacement pixel value in the same frame, on the same row, and a predetermined number of pixels from the current pixel location, and a replacement unit for replacing the defective pixel value with the consistent replacement pixel value.

21. (currently amended) A method for correcting at least one defective pixel in an array of pixels having a first predetermined number of rows and a second predetermined number of columns comprising:

receiving a current pixel location;

receiving a defective pixel location that does not vary from frame to frame;

wherein receiving a defective pixel location ~~includes~~ includes:

employing a table for storing a plurality of defective pixel locations;

wherein the table includes a last entry having a row value and a column value; wherein employing a table for storing a plurality of defective pixel locations ~~includes~~ includes:

setting the row value of the last entry in the table to a value that

S.N. 09/834,061
William L. Post
Atty Dkt 10003807-1

is greater than the first predetermined number of rows; and
setting the column value of the last entry in the table to a value
that is greater than the second predetermined number of columns;
when the current pixel location is not a defective pixel location,
providing a received pixel value as output pixel value; and
when the current pixel location is a defective pixel location, providing a
consistent replacement pixel value as the output pixel value.

22. (currently amended) The method of claim 21 wherein the method eliminates one of artifacts that stem from inconsistent detection of defective pixel pixels from frame to frame and artifacts that stem from inconsistent replacement of defective pixels.

23. (previously presented) The method of claim 21 wherein the defective pixel locations are stored in the table in a sorted order; wherein a search of the table to determine if a current pixel location is a defective location is obviated.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.